

SPECIFICATION

ENGINE AND TRANSMISSION	
Type	Liquid cooled, 8 valve, SOHC, 270° crank angle parallel twin
Capacity	900 cc
Bore	3.33 in (84.6 mm)
Stroke	3.15 in (80 mm)
Compression	11.0:1
Max Power EC	65 PS / 64.1 bhp (47.8 kW) @ 7250 rpm
Max Torque EC	59.0 lb-ft (80 Nm) @ 3250 rpm
System	Multipoint sequential electronic fuel injection, three riding modes
Exhaust	Brushed stainless steel 2 into 2 exhaust system with twin high-level brushed stainless steel silencers
Final Drive	X ring chain
Clutch	Wet, multi-plate, slip & assist
Gearbox	5 speed

CHASSIS	
Frame	Tubular steel, with steel cradles
Swingarm	Twin-sided, fabricated aluminum
Front Wheel	Spoked, aluminum rim, 32-spoke, 19 x 2.5 in
Rear Wheel	Spoked, aluminum rim, 32-spoke, 17 x 4.25 in
Front Tire	100/90-19
Rear Tire	150/70 R17
Front Suspension	Showa 1.69 in (43 mm) upside-down forks, 120 mm wheel travel
Rear Suspension	Twin Showa RSUs with external reservoirs and adjustable preload. 4.72 in (120 mm) wheel travel

Front Brakes	Single 12.6 in (320 mm) floating disc, four-piston radial caliper, OCABS
Rear Brakes	Single 10 in (255mm) fixed disc, Nissin two-piston floating caliper, OCABS
Instrument Display and Functions	LCD multi-function instruments with integrated color TFT screen

DIMENSIONS & WEIGHTS	
Length	83.1 in (2111 mm)
Width Handlebars	33.6 in (853 mm)
Height Without Mirror	46.4 in (1178 mm)
Seat Height	31.1 in (790 mm)
Wheelbase	56.9 in (1445 mm)
Rake	25.8 °
Trail	4.41 in (112 mm)
Tank Capacity	3.17 gal (12 liters)
Wet Weight	487.2 lbs (221 kg)

SERVICE	
Service Interval	10,000 miles (16,000km)/12 months (whichever comes first)

CONSUMPTION AND EMISSIONS	
Fuel Consumption	4.0 liters / 100 km
CO2 Figures	95 g/km EURO 5+ CO2 emissions and fuel consumption data are measured according to regulation 168/2013/EC. Figures for fuel consumption are derived from specific test conditions and are for comparative purposes only. They may not reflect real driving results.